

CHARACTER:

1.Physical performance

- a、Excellent mechanical properties
- b、Excellent thermal stability
- c、Low temperature soft good performance
- d、Good flame retardancy
- e、high of resistance to chemicals
- f、Chemistry stability is good

2.Electrical Properties

- a、Electrical insulation good
- b、Good the dielectric properties

3.Processing properties

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、According to UL standard design

4.Environmental protection

- a、low smoke, non-halogen
- b、ROHS/REACH compliant


SHOULD BE USED:

Internal wiring of TV receivers or where the acceptability has been determined by Underwriters Laboratories.

REFERENCE:

UL758-2010、UL1581-2009

Outline:



Wire structure description:
 Conductor: Tinned /Bare copper ;
 Insulation materials:HDPE insulation
 Jacket materials: XLPE jacket

Internal wiring of Appliances. Conductor temperature not over 105°C XLPE insulated wire
 Rated temperature: 105°C rated voltage: 10KV-DC

STYLE	AWG	Conductor size (No./ mm) ±0.005mm	Conductor resistance 20°C (Ω/Km)	Conductor Dia.(mm)	jacket thickness Nom. (mm)	Jacket thickness (mm)	Overall diameter (mm)
3239	16	26/0.254	14.6	1.5	0.33	0.46	3.10±0.15
	18	16/0.254	23.2	1.17	0.33	0.46	2.75±0.10
	20	21/0.18	36.7	0.95	0.33	0.46	2.50±0.10
	22	17/0.16	59.4	0.76	0.33	0.46	2.34±0.10
	22	7/0.254	59.40	0.78	0.33	0.46	2.36±0.10
	24	11/0.16	94.2	0.6	0.33	0.46	2.20±0.10
	26	7/0.16	150	0.48	0.33	0.46	2.06±0.10
	28	7/0.127	239	0.38	0.33	0.46	1.96±0.10

Marking: E211048 AWM STYLE 3239 NO.AWG 105°C 10KV-DC VW-1 QIFURUI
 c AWM I A 105°C 10KV-DC FT2 -LF-

SAE COLOR SERIES

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

PACKAGE

*PACKAGE					
Part No.	Packing- FT/roll				
16AWG	<input type="checkbox"/> 100FT	<input type="checkbox"/> 500FT	<input checked="" type="checkbox"/> 1000FT	<input type="checkbox"/> 2000FT	
18~28AWG	<input type="checkbox"/> 100FT	<input type="checkbox"/> 500FT	<input type="checkbox"/> 1000FT	<input checked="" type="checkbox"/> 2000FT	
According to customer requirements for packaging packaging					